

## CH1000B-8x100



|               |            |
|---------------|------------|
| Content       | 1000 cc    |
| Top out       | 247x148 mm |
| Top in        | 226x127 mm |
| Bottom        | 204x105 mm |
| Useful Height | 44 mm      |
| Height        | 54 mm      |
| Nett weight   | 13,55 gr   |

**Tolerances :**

\* Thickness +/- 8% (EN546-3)

\* Weight -8%

\* Dimensions +/- 1mm

### EAN-13

#### CARTON/BOX

| Quantity | EAN-13            |
|----------|-------------------|
| 8 x 100  | 5 410 797 301 153 |

#### POLYBAG

| Quantity | EAN-13            |
|----------|-------------------|
| 100      | 5 410 797 301 122 |

| Packaging | Quantity<br>ctn | Dimensions Ctn |       |       | Tare Ctn<br>(kg) | Net Ctn<br>(kg) | Gross Ctn<br>(kg) | Ctn/Layer | Layer/Pal | Ctn/Pal | Quantity<br>palet | Height Pal<br>(m) | Gross Pal<br>(kg) |
|-----------|-----------------|----------------|-------|-------|------------------|-----------------|-------------------|-----------|-----------|---------|-------------------|-------------------|-------------------|
|           |                 | L(mm)          | W(mm) | H(mm) |                  |                 |                   |           |           |         |                   |                   |                   |
| 8 x 100   | 800             | 585            | 384   | 440   | 0,93             | 10,84           | 11,77             | 4         | 5         | 20      | 16.000            | 2,35              | 255,46            |

### Complies with

- \* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- \* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
- \* Regulation 2006/2023/EC

### Proper conditions of transport, storage and use

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- \* Avoid moisture (wetness, condensation, ...)
- \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
- \* Give the aluminium appropriate time to climatise by opening boxes a few hours prior to use.
- \* Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
- \* It is recommended to avoid contact with strongly acidic, salty and/or alkaline products.
- \* The temperature and contact time have a significant influence on the suitability of uncoated aluminium foil containers for specific applications. Therefor the relevant user/customer/filler/packer should ascertain the suitability of the product for its application.

*Note : Full detailed information can be found on the certificate of conformity (available upon request)*