

## S33 100

|               |                           |
|---------------|---------------------------|
| Content       | - cc                      |
| Top out       | 333x233 mm                |
| Top in        | - mm                      |
| Bottom        | 247x147 mm                |
| Useful Height | mm                        |
| Height        | mm                        |
| Nett weight   | 22,92 gr                  |
| Lubrification | 200-300 mg/m <sup>2</sup> |
| Alloy         | 8666 H21/8006 H0          |



|            |                   |
|------------|-------------------|
|            | EAN-13            |
| CARTON/BOX |                   |
| Quantity   | EAN-13            |
| 100        | 5 410 797 503 304 |

|          |        |
|----------|--------|
| POLYBAG  |        |
| Quantity | EAN-13 |

Tolerances : thickness +/- 10%; weights -10%; dimensions +/- 1mm

| Packaging | Quantity<br>ctn | Dimensions Ctn |       |       | Tare Ctn<br>(kg) | Net Ctn<br>(kg) | Gross Ctn<br>(kg) | Ctn/Layer | Layer/Pal | Ctn/Pal | Quantity<br>palet | Height Pal<br>(m) | Gross Pal<br>(kg) |
|-----------|-----------------|----------------|-------|-------|------------------|-----------------|-------------------|-----------|-----------|---------|-------------------|-------------------|-------------------|
|           |                 | L(mm)          | W(mm) | H(mm) |                  |                 |                   |           |           |         |                   |                   |                   |
| 100       | 100             | 412            | 270   | 352   | 0,50             | 2,29            | 2,79              | 8         | 5         | 40      | 4.000             | 1,91              | 131,68            |

### Made of materials that complies with :

- \* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- \* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
- \* Regulation 2006/2023/EC

### Lubrification complies with :

- \* US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

### Proper conditions of transport, storage and use

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- \* Avoid moisture (wetness, condensation, ...)
- \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
- \* Open packaging 2-3 hours prior to use.
- \* Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
- \* It is recommended to avoid contact with strongly acidic and/or alkaline products.
- \* The suitability of uncoated aluminium foil containers for specific applications should be ascertained by the relevant user/customer/packer.