

## RR0100-30x100

Content	100 cc
Top out	100 mm
Top in	90 mm
Bottom	70 mm
Useful Height	18 mm
Height	20 mm
Nett weight	1,8 gr
Thickness	50 µm
Alloy	UNI 8006-8001-3003
Lubrication	300-400 mg/m <sup>2</sup>



EAN-13	
<b>CARTON/BOX</b>	
<b>Quantity</b>	<b>EAN-13</b>
30 x 100	5 410 797 001 909

<b>POLYBAG</b>	
<b>Quantity</b>	<b>EAN-13</b>
100	5 410 797 001 923

Tolerances : thickness +/- 5%; weights -5%; dimensions +/- 1mm

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
30 x 100	3.000	400	400	550	1,08	5,40	6,48	6	4	24	72.000	2,35	175,52

### Made of materials that complies with :

- \* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- \* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"

### Lubrication complies with :

- \* US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

### Proper conditions of transport and storage

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible
- \* Avoid moisture (wetness, condensation, ...) and store in closed room as dry as possible.
- \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.

### Remarks

- \* Aluminium is a non-toxic metal.
- \* It is recommended to avoid strongly acid and/or saline products
- \* Filling material producer should judge the suitability of the packaging material for each used purpose