

## RR0277-600



Content	1250 cc
Top out	277 mm
Top in	261 mm
Bottom	247 mm
Useful Height	23 mm
Height	24 mm
Nett weight	15,47 gr
Thickness	68 µm
Alloy	8666 H25/8006 H24
Lubrification	300-400 gr/m <sup>2</sup>

Tolerances : thickness +/- 5%; weights -5%; dimensions +/- 1mm

EAN-13	
CARTON/BOX	
Quantity	EAN-13
600	5 410 797 102 118

POLYBAG	
Quantity	EAN-13

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
600	600	790	390	545	1,51	9,28	10,79	3	4	12	7.200	2,33	149,50

### Made of materials that complies with :

- \* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- \* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"

### Lubrification complies with :

- \* US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

### Proper conditions of transport and storage

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible
- \* Avoid moisture (wetness, condensation, ...) and store in closed room as dry as possible.
- \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.

### Remarks

- \* Aluminium is a non-toxic metal.
- \* It is recommended to avoid strongly acid and/or saline products
- \* Filling material producer should judge the suitability of the packaging material for each used purpose