

## CR2400-100

|               |                           |
|---------------|---------------------------|
| Content       | 2400 cc                   |
| Top out       | 322x262 mm                |
| Top in        | 298x238 mm                |
| Bottom        | 280x220 mm                |
| Useful Height | 39 mm                     |
| Height        | 43 mm                     |
| Nett weight   | 33,35 gr                  |
| Lubrification | 300-400 mg/m <sup>2</sup> |
| Alloy         | 3005 H0                   |



|            |                   |
|------------|-------------------|
|            | EAN-13            |
| CARTON/BOX |                   |
| Quantity   | EAN-13            |
| 100        | 5 410 797 202 900 |

|          |        |
|----------|--------|
| POLYBAG  |        |
| Quantity | EAN-13 |

Tolerances : thickness +/- 8%; weights -8%; dimensions +/- 1mm

| Packaging | Quantity<br>ctn | Dimensions Ctn |       |       | Tare Ctn<br>(kg) | Net Ctn<br>(kg) | Gross Ctn<br>(kg) | Ctn/Layer | Layer/Pal | Ctn/Pal | Quantity<br>palet | Height Pal<br>(m) | Gross Pal<br>(kg) |
|-----------|-----------------|----------------|-------|-------|------------------|-----------------|-------------------|-----------|-----------|---------|-------------------|-------------------|-------------------|
|           |                 | L(mm)          | W(mm) | H(mm) |                  |                 |                   |           |           |         |                   |                   |                   |
| 100       | 100             | 535            | 340   | 270   | 0,30             | 3,34            | 3,64              | 4         | 6         | 24      | 2.400             | 1,77              | 107,24            |

### Made of materials that complies with :

- \* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- \* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
- \* Regulation 2006/2023/EC

### Lubrification complies with :

- \* US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

### Proper conditions of transport, storage and use

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- \* Avoid moisture (wetness, condensation, ...)
- \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
- \* Open packaging 2-3 hours prior to use.
- \* Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
- \* It is recommended to avoid contact with strongly acidic and/or alkaline products.
- \* The suitability of uncoated aluminium foil containers for specific applications should be ascertained by the relevant user/customer/packer.