

RR0079-20x100

| | |
|---------------|---------------------------|
| Content | 100 cc |
| Top out | 79 mm |
| Top in | 72 mm |
| Bottom | 54 mm |
| Useful Height | 34 mm |
| Height | 35 mm |
| Nett weight | 2,22 gr |
| Lubrification | 300-400 mg/m ² |
| Alloy | 8021 H24 |



| EAN-13 | |
|-------------------|-------------------|
| CARTON/BOX | |
| Quantity | EAN-13 |
| 20x100 | 5 410 797 105 218 |

| | |
|-----------------|-------------------|
| POLYBAG | |
| Quantity | EAN-13 |
| 100 | 5 410 797 105 225 |

Tolerances : thickness +/- 10%; weights -10%; dimensions +/- 1mm

| Packaging | Quantity ctn | Dimensions Ctn | | | Tare Ctn (kg) | Net Ctn (kg) | Gross Ctn (kg) | Ctn/Layer | Layer/Pal | Ctn/Pal | Quantity palet | Height Pal (m) | Gross Pal (kg) |
|-----------|-----------------|----------------|-------|-------|------------------|-----------------|-------------------|-----------|-----------|---------|-------------------|-------------------|-------------------|
| | | L(mm) | W(mm) | H(mm) | | | | | | | | | |
| 20x100 | 2.000 | 365 | 275 | 385 | 0,15 | 4,44 | 4,59 | 8 | 5 | 40 | 80.000 | 2,08 | 203,60 |

Made of materials that complies with :

- * Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- * European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
- * Regulation 2006/2023/EC

Lubrification complies with :

- * US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

Proper conditions of transport, storage and use

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- * Avoid moisture (wetness, condensation, ...)
- * Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
- * Open packaging 2-3 hours prior to use.
- * Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
- * It is recommended to avoid contact with strongly acidic and/or alkaline products.
- * The suitability of uncoated aluminium foil containers for specific applications should be ascertained by the relevant user/customer/packer.