

## CH0700-10x100



Content	700 cc
Top out	205x110 mm
Top in	186x91 mm
Bottom	160x69 mm
Useful Height	49 mm
Height	58 mm
Nett weight	9,87 gr

**Tolerances :**

\* Thickness +/- 8% (EN546-3)

\* Weight -8%

\* Dimensions +/- 1mm

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
10 x 100	1.000	425	350	470	0,68	9,87	10,55	6	4	24	24.000	2,03	273,20

### EAN-13

#### CARTON/BOX

Quantity	EAN-13
10 x 100	5 410 797 300 514

#### POLYBAG

Quantity	EAN-13
100	5 410 797 300 521

### Complies with

- \* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
  - \* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
  - \* Regulation 2006/2023/EC
- Proper conditions of transport, storage and use**
- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
  - \* Avoid moisture (wetness, condensation, ...)
  - \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
  - \* Give the aluminium appropriate time to climatise by opening boxes a few hours prior to use.
  - \* Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
  - \* It is recommended to avoid contact with strongly acidic, salty and/or alkaline products.
  - \* The temperature and contact time have a significant influence on the suitability of uncoated aluminium foil containers for specific applications. Therefor the relevant user/customer/filler/packer should ascertain the suitability of the product for its application.

*Note : Full detailed information can be found on the certificate of conformity (available upon request)*