TECHNICAL SHEET

Welvaartstraat 14
B-2200 HERENTALS

passion for alu packaging

RR0175-1000

Content	400 cc
Top out	175 mm
Top in	160 mm
Bottom	145 mm
Useful Height	23 mm
Height	25 mm
Nett weight	5,90 gr
Alloy	8666 H25/8006 H24
Lubrification	300-400 mg/m²

EAN-13

CARTON/BOX

Quantity	*EAN-13*
1000	5 410 797 101 302

POLYBAG

Quantity	*EAN-13*

Tolerances : thickness +/- 8% (EN546-3) ; weights -8%; dimensions +/- 1mm

Packaging	*Quantity*	*Dimensions Ctn*			*Tare Ctn*	*Net Ctn*	*Gross Ctn*	*Ctn/Layer*	*Layer/Pal*	*Ctn/Pal*	*Quantity*	*Height Pal*	*Gross Pal*
	ctn	*L(mm)*	*W(mm)*	*H(mm)*	*(kg)*	*(kg)*	*(kg)*				*palet*	*(m)*	*(kg)*
1000	**1.000**	**425**	**350**	**470**	**0,68**	**5,90**	**6,58**	**6**	**4**	**24**	**24.000**	**2,03**	**177,92**

Made of materials that complies with :

* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and reapealing Directive 89/109/EEC
* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
* Regulation 2006/2023/EC

Lubrification complies with :

* US Food and Drug Administration FDA21 CFR Ch1 § 172.830 or 178.3910 or 178.3570

Proper conditions of transport, storage and use

* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
* Avoid moisture (wetness, condensation, …)
* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
* Open packaging 2-3 hours prior to use.
* Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
* It is recommended to avoid contact with strongly acidic and/or alkaline products.
* The suitability of uncoated aluminium foil containers for specific applications should be ascertaineded by the relevant user/customer/packer.