TECHNICAL SHEET

Welvaartstraat 14
B-2200 HERENTALS

Aluvin
passion for alu packaging

RR0075-23x100

Content	150 cc
Top	85 mm
out Top in	76 mm
Bottom	67 mm
Useful	33 mm
Height	40 mm
Height	2,86 gr

EAN-13

CARTON/BOX

Quantity	*EAN-13*
15 x 100	5 410 797 100 466

POLYBAG

Quantity	*EAN-13*
100	5 410 797 100 428

Tolerances :

**** Tickness +/- 8% (EN546-3)***

**** Weight -8%***

**** Dimensions +/- 1mm***

Packaging	*Quantity ctn*	*Dimensions Ctn*			*Tare Ctn (kg)*	*Net Ctn (kg)*	*Gross Ctn (kg)*	*Ctn/Layer*	*Layer/Pal*	*Ctn/Pal*	*Quantity palet*	*Height Pal (m)*	*Gross Pal (kg)*
		L(mm)	*W(mm)*	*H(mm)*									
15 x 100	**1.500**	**535**	**360**	**410**	**0,75**	**4,29**	**5,04**	**4**	**5**	**20**	**30.000**	**2,20**	**120,88**

Complies with

* Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and reapealing Directive 89/109/EEC

* European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"

* Regulation 2006/2023/EC

Proper conditions of transport, storage and use

* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.

* Avoid moisture (wetness, condensation, …)

* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.

* Give the aluminium appropirate time to climatise by opening boxes a few hours prior to use.

* Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.

* It is recommended to avoid contact with strongly acidic, salty and/or alkaline products.

* The temparature and contact time have a significant influence on the suitability of uncoated aluminium foil containers for specific applications. Therefor the relevant user/customer/filler/packer should ascertain the suitabilty of the product for its application.

Note : Full detailed information can be found on the certificate of conformity (available upon request)

Versie 10 - 01/05/2016