

CH0470-10x100

Content	470 cc
Top out	147x122 mm
Top in	129x104 mm
Bottom	108x82 mm
Useful Height	43 mm
Height	49 mm
Nett weight	5,80 gr



	EAN-13
CARTON/BOX	
Quantity	EAN-13
10 x 100	5 410 797 300 354

	EAN-13
POLYBAG	
Quantity	EAN-13
100	5 410 797 300 323

Tolerances :

* *Thickness +/- 8% (EN546-3)*

* *Weight -8%*

* *Dimensions +/- 1mm*

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
10 x 100	1.000	410	460	270	0,54	5,80	6,34	4H + 2V	8H + 5V	42	42.000	2,31	286,28

Complies with

- * Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- * European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
- * Regulation 2006/2023/EC

Proper conditions of transport, storage and use

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- * Avoid moisture (wetness, condensation,...)
- * Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
- * Give the aluminium appropriate time to climatise by opening boxes a few hours prior to use.
- * Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
- * It is recommended to avoid contact with strongly acidic, salty and/or alkaline products.
- * The temperature and contact time have a significant influence on the suitability of uncoated aluminium foil containers for specific applications. Therefor the relevant user/customer/filler/packer should ascertain the suitability of the product for its application.

Note : Full detailed information can be found on the certificate of conformity (available upon request)