

CR0825-10x100

Content	825 cc
Top out	201x137 mm
Top in	190x120 mm
Bottom	160x95 mm
Useful Height	45 mm
Height	48 mm
Nett weight	8,59 gr



EAN-13	
CARTON/BOX	
Quantity	EAN-13
10 x 100	5 410 797 202 412

POLYBAG	
Quantity	EAN-13
100	5 410 797 202 429

Tolerances :

* Thickness +/- 8% (EN546-3)

* Weight -8%

* Dimensions +/- 1mm

Packaging	Quantity ctn	Dimensions Ctn			Tare Ctn (kg)	Net Ctn (kg)	Gross Ctn (kg)	Ctn/Layer	Layer/Pal	Ctn/Pal	Quantity palet	Height Pal (m)	Gross Pal (kg)
		L(mm)	W(mm)	H(mm)									
10 x 100	1.000	585	384	440	0,93	8,59	9,52	4	5	20	20.000	2,35	210,46

Complies with

- * Regulation **2004/1935/EC** on material and articles intended to come into **contact with food** and repealing Directive 89/109/EEC
- * European Standard **EN602** "Aluminium and aluminium alloys - Wrought products - Chemical composition of semi products used for the fabrication of articles for use in **contact with food** (Version 07/2004)"
- * Regulation 2006/2023/EC

Proper conditions of transport, storage and use

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- * Avoid moisture (wetness, condensation, ...)
- * Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms.
- * Give the aluminium appropriate time to climatise by opening boxes a few hours prior to use.
- * Used aluminium alloy can be used within temperature range : -40°C / +250°C (max 60 min). However, content of filled containers can influence these limits.
- * It is recommended to avoid contact with strongly acidic, salty and/or alkaline products.
- * The temperature and contact time have a significant influence on the suitability of uncoated aluminium foil containers for specific applications. Therefore the relevant user/customer/filler/packer should ascertain the suitability of the product for its application.

Note : Full detailed information can be found on the certificate of conformity (available upon request)